

SEC - SLE 07C DC SMC



FEATURES

- 7" Colour TFT LCD display
- Slimline Series - Slim & Sleek Design
- Hands Free Operation
- Micro Controller Based with digital circuit
- Can connect up to 4 monitors (1 main monitor and 3 sub-monitors)
- Can connect 2 cameras
- Can connect with surface mount or flush mount camera
- External CCTV camera can be connected if using one VDP outdoor camera
- Exceptional audio clarity & volume
- Inbuilt Security Alarm
- TV output to see parallel image on TV screen
- Can attach optional RF receiver for remote operation (optional, separate for each monitor)
- External Switch Mode Power Supply (SMPS) required
- RS 485 connectivity between monitors, cameras and modules
- Monitor Function
- Door Lock Control
- 10 Amp relay with normally open (NO) and normally closed (NC) contacts for different types of locks
- Lock can be connected from outdoor camera and lock control module
- Alarm out - can connect to intruder alarm or auto dialer
- Tamper spring in camera with tamper alarm
- White LEDs for night vision
- Low power consumption
- Includes 1 Monitor and 1 Outdoor Surface Mount Camera

TECHNICAL SPECIFICATIONS

Indoor Monitor	
Model	SEC - SLE 07C DC SMC
Display	7" Colour TFT LCD
Power Supply	External SMPS
Power Consumption	16W Max
Communication	Hands Free Half Duplex
Button Functions	Monitor 1, 2, Talk, Lock, Alarm, Display Settings and Volume
Mount type	Surface Mount
Mounting Bracket	Included
Maximum wire length from camera to last monitor	100m
TFT Resolution	1440 (H) x 234 (V)
Wiring to Camera	1 Coaxial + 4
Wiring to Sub Monitor	1 Coaxial + 3
Connectors	Terminal Block
Lock Connection Source	Connection from Outdoor Camera & External Lock Control Module
Bell Sound	Ding Dong
Security Alarm Sound	Continuous Ding Dong in Monitor & Police Siren in Camera
Operating Temperature	5°C to 60°C
Dimensions (max.)	227mm (H) X 178mm (W) X 26mm (D)
Net Weight	600 gm
Outdoor Surface Mount Camera	
Power Supply	From main monitor
Power Consumption	2.75W max
Camera	Surface Mount: CCD 1/4" 420TVL
Minimum Illumination	0.1 Lux - F2.0
Lens	3.6mm F2.0
Night Vision	White LED's with 1mtr visibility
Connectors	Surface Mount: Terminal Block
Mount Type	Surface Mount: Surface / Partially Flush
Mounting Frame	Surface Mount: Included
Operating Temperature	5°C to 60°C
Siren Sound	Police Siren
Lock Type	NO / NC Type Electronic, Strike, Release, Electromagnetic, Others
Lock Power Supply	External, Not Included
Bell Sound	Ding Dong
Dimensions (max.)	Surface Mount: 127mm (H) X 96mm (W) X 36mm (D), 39.5mm (D) with Surface Mount Bracket
Weight	Surface Mount : 175 gm