

DS-2CC102/112/192P(N)-IR IR Bullet Camera



Key Features

- Compact design
- 1/3" Sony CCD
- Low illumination
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Internal synchronization
- IP66 rating

Specifications

	DS-2CC102P(N)-IR	DS-2CC112P(N)-IR	DS-2CC192P(N)-IR
Camera			
Image sensor	1/3" Sony CCD		
Signal system	PAL / NTSC		
Effective pixels	PAL: 500 (H) × 582 (V) NTSC: 510 (H) × 492 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)
Min. illumination	0.1 lux@F1.2, AGC on, 0 lux with IR 0.2 lux@F1.8, AGC on, 0 lux with IR		
Shutter time	PAL: 1/50s ~ 1/100,000s NTSC: 1/60s ~ 1/100,000s		
Lens	6 mm @F1.8 (3.6mm, 2.8mm optional) Angle of view: 47° (6mm)		
Lens mount	M12		
Day & night	Electronic		
Horizontal resolution	420 TVL	480 TVL	540 TVL
Synchronization	Internal synchronization		
Video output	1Vp-p composite output (75Ω / BNC)		
S/N ratio	More than 48dB		
BLC	On		
General			
Operating conditions	-10 °C ~ 60 °C (14 °F ~ 140 °F) Humidity 90% or less (non-condensing)		
Power supply	12 VDC ± 10%		
Power consumption	3W max.		
Weather-proof rating	IP66		
IR range	Approx. 10 ~ 20m		
Dimensions	Φ 65 × 104mm (Φ 2.56" × 4.09")		
Weight	250g (0.55 lbs)		

Available models

DS-2CC102P-IR, DS-2CC102N-IR, DS-2CC112P-IR, DS-2CC112N-IR, DS-2CC192P-IR, DS-2CC192N-IR

Dimensions

